

TECHNICAL DATA SHEET

TECHNISCHES DATENBLATT



DX MF 301

GENERAL INFORMATION

Mounting fluid for an efficient wet bonding of self-adhesive foils. DX MF 301 is ready-to-use and optimized for our self-adhesive UV-protection yellow foil YSA520.

MAIN FEATURES

- Fast and easy bonding of self-adhesive foils such as our yellow foil YSA520.
- The foil keeps repositionable during bonding for a while.
- Leaves no visible or interfering residues.
- Allows a strong final bonding of the foil to the window.

CHEMICAL CHARACTERISTICS

A nonflammable aqueous solution of anionic and nonionic surfactants and alcohols. No labeling requirement. A Material Safety Data Sheet according to EU regulations is available.

FIRST AID

In case of contact with the eye, rinse thoroughly with cold water.

PROCESSING

Clean the surface (window) thoroughly and spray evenly with the mounting fluid DX MF 301. Attach the self-adhesive foil to be bonded with the adhesive on the still moist surface, squeeze the excess liquid thoroughly from the gap between foil and window (a suitable squeegee with felt insert is also available from us). Wipe away remains of mounting fluid DX MF 301 with a soft, absorbent cloth. A possible whitening of the film vanishes depending on temperature and room humidity within a few days.

SALES UNITS

Article-number:	Sales units
GEZBDX301	800 ml (Sprühflasche)
GEZ5DX305	5.000 ml (Kanister)

Version 1 Seite 1 | 2



TECHNICAL DATA SHEET TECHNISCHES DATENBLATT



Further Information

All data and information relate to the best of our knowledge and are based on measurement and experience. It remains in your responsibility to check the suitability of our yellow foil for the intended use of it. Our products are regularly quality-tested and further developed. We therefore reserve the right to adjust without additional information, the chemical composition or physical characteristics of new knowledge.

For any further information please contact our technical advisory.

Your request by E-Mail or Phone. E-Mail: <u>info@lithoprotect.com</u> Phone: +49 (0) 731 3608 0916

The brand Lithoprotect® belongs to:



durXtreme GmbH Nicolaus-Otto-Str. 39 89079 Ulm Germany

Version 1 Seite 2 | 2